



US006056414A

# United States Patent [19] Krieger

[11] Patent Number: 6,056,414  
[45] Date of Patent: May 2, 2000

## [54] PORTABLE LIGHT WITH STAND

- [75] Inventor: Michael Krieger, Miami Beach, Fla.  
[73] Assignee: Vector Products, Inc., Hollywood, Fla.  
[21] Appl. No.: 09/275,427  
[22] Filed: Mar. 24, 1999  
[51] Int. Cl.<sup>7</sup> ..... F21V 21/40  
[52] U.S. Cl. .... 362/184; 362/190; 362/399  
[58] Field of Search ..... 362/184, 190,  
362/197, 208, 399; D26/45

## [56] References Cited

### U.S. PATENT DOCUMENTS


- |           |         |            |           |
|-----------|---------|------------|-----------|
| 5,558,430 | 9/1996  | Booty, Jr. | 362/184   |
| 5,859,582 | 1/1999  | Yuen       | 362/184 X |
| 5,971,562 | 10/1999 | Yang       | 362/184   |

Primary Examiner—Stephen Husar  
Attorney, Agent, or Firm—Venable; Robert Kinberg

## [57] ABSTRACT

A portable light includes first and second d.c. lamps. A first housing portion has longitudinal access and encloses the first lamp while projecting a first light beam in a direction of longitudinal access. The first housing portion has a exterior surface contour and includes a compartment containing an electrical device connectable to a d.c. power supply connectable in circuit with the first lamp. A second housing portion is the shape of a hand grip and extends from first side of the first housing portion in a direction transversed to the longitudinal access to the first housing portion. The second housing portion encloses the second lamp which is connectable in circuit with the electrical device for projecting a second light beam in the direction forming at an angle with the longitudinal access of the first housing portion. A support is pivotally connected to the first housing portion and is pivotable between a closed position in which the support has a shape which generally conforms to the contour of the exterior surface of the first housing portion and an open position in which the support forms a stand extending from an opposite side of the first housing portion from that of the first side of the first housing portion for stabilizing the portable light source on a surface so that one of the first and second lamps can be directed to a work area.

11 Claims, 3 Drawing Sheets



FOR 22587660